



CABLE

PVC round cable LIYY 2x0.14mm², 350V
colour grey, colour of wires brown/white
ends 5±1 mm stripped and tinned

*PVC Rundkabel LIYY 2x0.14 mm², 350V
Mantelfarbe grau, Aderfarben braun/weiß
Enden 5±1 mm abisoliert und verzinkt*

MATERIAL

stem- polyamid black
nut- polyamid black
float- polyamid black
O-ring- nitril cautchuc black

*Schaft- Polyamid schwarz
Mutter- Polyamid schwarz
Schwimmer- Polyamid schwarz
O-Ring nitril Kautschuk schwarz*

Float specific density - approx. 0.7 g/cm³
Spezifisches Schwimmergewicht ca. 0.7 g/cm³

MARKING

MEDER-Label, Type
Production code EN60062/
Factory code

*MEDER-Logo, Typ
Produktionscode
EN60062/Fertigungsstätte*



dimensions / Abmessungen (mm)
unspecified tolerances acc. to DIN ISO 2768-m

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peack AC			320	VDC
operating ampere	DC or Peack AC			1	A
Switching current	DC or Peack AC			0,4	A
Sensor-resistance	measured with 40% overdrive			400	mOhm
Housing material			Polyamid		
Case color			black		
Sealing compound			Polyurethan		

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C
safety class	DIN EN 60529		IP68, until the thread		

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ			round cable		
Cable material			PVC		
Cross section			0,14 mm ²		

General data	Conditions	Min	Typ	Max	Unit
Mounting advice			over 5m cable, a series resistor is recommended.		
Tightening torque				3	Nm